
# INSTRUCTIONS FOR

The Carburetter of



**Records & Successes** 

## TYPES IS G.P., I (Series 316) 10 G.P., 5 G.P.



With fixed or remotely-mounted type 302 top-feed Float Chamber and SUITABLE FOR USE WITH ALL GRADES OF RACING FUELS.

#### KEY TO ILLUSTRATION

- Banjo (Twin), 90°, horizontal petrol pipe connections.
- Banjo Nut with hole for lock wire.
- Tickler.
- Mixing Chamber Cap. A screwed ring.
  Lock Spring for Mixing Chamber cap.
  Throttle Cable.
  Throttle Cable Adjuster with lock nut.
- D. E. F. G.

- Air Cable for mixture control.
  Air Cable Adjuster with lock nut.

- Flange Attachment to Engine.
  Pilot Needle, adjustment for slow running.
  Jet Holder Plug Screw, remove to get at main jet.
  Jet Holder, also holds float chamber to mixing chamber

#### TECHNICAL INFORMATION.

Туре	CHOKE BORES MEASURED BEHIND THROTTLE VALVES	Throttle Diameter	FLANGE BOLT- HOLE CENTRES	Mixing Chamber to Face of Flange	
15 G.P. 10 G.P. 5 G.P.	$\begin{array}{cccccccccccccccccccccccccccccccccccc$	$1\frac{1}{2}''$ $1\frac{5}{8}''$ $1\frac{13}{16}''$	} 2" 65 m.m.		

\*Straight-through Bore with no swell.—see note page 3.

### TUNING SPARES.

CAMPBELL COLLEGE COLLEGE	AND THE RESIDENCE OF THE PARTY	10111110		week particular and the second			
Туре	THROTTLE VALVES	Throttle Needles		MAIN JETS	Needle Jets	Air Jets	
15 G.P.	15 G.P. Cutaway 3 to 8 Part No. 316/104	Standard G.P. Part No. 316/007	Weak G.P.6 316/030	Inter- changeable	changeable ch Type G.P. Ty	Inter- changeable Type G.P.	
10 G.P.	10 G.P. Cutaway 3 to 8 Part No. 316/010	G.P. Part No. 316/007	G.P.6 316/030	Type T.T. Part No.	316/065   ·107"   ·109"	Part No. 316/052	
5 G.P.	5 G.P. Cutaway 3 to 8 Part No. 316/020	5 G.P. Part No. 316/146	5 G.P.6 316/029	3326	125″	). 310/032	

(THIS LIST IS PRINTED IN ENGLAND, AND IS ISSUED SUBJECT TO PRICES RULING AT THE DATE OF DELIVERY).

Witton, BIRMINGHAM, 6 Road, AMAL LTD., Holdford ENGLAND.

TELEPHONE: BIRCHFIELDS 4571 (6 lines).

TELEGRAMS: AMALCARB (PHONE), BIRMINGHAM.